

SMART LED DRIVERS & SMPS

POWERED BY



colossusworld.com



ABOUT COLOSSUS

At Colossus, we are your guiding light in the world of LED drivers. Our commitment to excellence and innovation shines through in every product we create. As a leading Indian LED driver brand, we take pride in our journey towards redefining the industry's standards.

Our product range is a testament to our dedication to quality and performance. With a focus on energy conservation and environmental sustainability, Colossus LED drivers are designed for reliability, durability, and eco-conscious living.

Discover a world of possibilities with our Smart Drivers and Standard Drivers. Our Smart Drivers, available in Isolated and Non-Isolated formats, harness cutting-edge technology for adaptability and convenience. They offer Surge Protection, High Voltage Protection, and compatibility with various smart modules, providing seamless control through mobile apps and smart home devices. For those seeking standard solutions, our Standard Drivers, in Isolated and Non-Isolated categories, provide reliable and efficient options.

Colossus is not just a brand; it's a beacon of innovation and reliability. Join us as we embark on a journey to illuminate your spaces with sustainable, energy-efficient, and technologically advanced LED drivers. Experience the brilliance of Colossus today.

Introducing

SNART LED DRIVERS & SMPS



CONTENT

PRO SERIES

PROFLEX

(Adjustable Current Drivers)

PRO STATIC

(Fixed Current Drivers)

PRO SPECTRA

(SMPS)

COLOSSUS®

Excellence inside



Where others follow, we lead with innovative R&D, impeccable manufacturing, and a supply chain that's a step ahead of tomorrow.







Research & **Development**

Manufacturing

Supply Chain

Approval Markings:













PROFLEX (Adjustable Current Drivers)




Functions

- · Smart Dimmable Constant Current Driver For LED Modules
- · Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- · Adjustable output current with Dip Switch.
- · Smooth Transition over wide range of CCT & Intensity
- · 1-100% Deep Dimming
- · High efficiency >88%(@100% Load)
- · Surge Protection 4KV

Model No.	Watt Pout	O/P Voltage Voυτ (V)	O/P Current lout (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
SS15IHIBLECCT40350A	8-14	27-40	200-350	>88	>0.98	4	2	92*57.5*31mm
SS24IHIBLE40600A (Only Dimming)	12-24	27-40	300-600	>88	>0.98	4	2	103*67.5*32mm
SS24IHIBLECCT40600A	12-24	27-40	300-600	>88	>0.98	4	2	103*67.5*32mm
SS40IHIBLE401000A (Only Dimming)	28-40	27-40	700-1000	>88	>0.98	4	2	103*67.5*32mm
SS40IHIBLECCT401000A	28-40	27-40	700-1000	>88	>0.98	4	2	103*67.5*32mm





Functions

- · Smart Dimmable Constant Current Driver For LED Modules
- · Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- · Adjustable output current with Dip Switch.
- · Smooth Transition over wide range of CCT & Intensity
- · 1-100% Deep Dimming
- · High efficiency >88%(@100% Load)
- Surge Protection 4KV

Model No.	Watt Pout	O/P Voltage Voυτ (V)	O/P Current Ιουτ (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
VS24IHIBLE40600A (Only Dimming)	12-24	27-40	300-600	>88	>0.98	4	2	150*40*28.5mm
VS24IHIBLECCT40600A	12-24	27-40	300-600	>88	>0.98	4	2	150*40*28.5mm
VS40IHIBLE401000A (Only Dimming)	28-40	27-40	700-1000	>88	>0.98	4	2	150*40*28.5mm
VS40IHIBLECCT401000A	28-40	27-40	700-1000	>88	>0.98	4	2	150*40*28.5mm










Spotlight

Downlight

Linear

Decorative

PRO STATIC (Fixed Current Drivers)



Functions

- \cdot Smart Dimmable Constant Current Driver For LED Modules
- · Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- · Smooth Transition over wide range of CCT & Intensity
- · 1-100% Deep Dimming
- · High efficiency Upto 86%(@100% Load)
- · Surge Protection Upto 4KV

Model No.	Watt Pout	O/P Voltage Vout (V)	O/P Current lout (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
LS08IHIBLECCT40200F	8	27-40	200	>86	>0.98	4	2	94.5*40*28mm
LS101HIBLECCT40250F	10	27-40	250	>86	>0.98	4	2	94.5*40*28mm
LS12IHIBLECCT40300F	12	27-40	300	>86	>0.98	4	2	94.5*40*28mm
LS151HIBLECCT40350F	14	27-40	350	>86	>0.98	4	2	94.5*40*28mm
LS15ISIBLECCT40350F	13	36	350	>85	>0.50	2.5	2	94.5*40*28mm





Functions

- Smart Dimmable Constant Current Driver For LED Modules
- \cdot Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- · Smooth Transition over wide range of CCT & Intensity
- · 1-100% Deep Dimming
- · High efficiency >88%(@100% Load)
- · Surge Protection upto 4KV

Model No.	Watt Pout	O/P Voltage Vout (V)	O/P Current Ιουτ (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
SS15NSIBLECCT75200F	12-15	60-75	200	>88	>0.50	2.5	2	79*38*26.5mm
SS15NHIBLECCT75200F	12-15	60-75	200	>88	>0.98	4	2	79*38*26.5mm
SS15NSIBLECCT50300F	9-15	30-50	300	>88	>0.50	2.5	2	79*38*26.5mm
SS15NHIBLECCT50300F	9-15	30-50	300	>88	>0.98	4	2	79*38*26.5mm

COLOSSUS³ Model No. Excellence inside VS36NHBLECCT72450F Input Us. : 240/MC, 6546 Is. 156A | Proc. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/M | X = 2.0 | Output Us. : 20/MC, 6546 Is. | 260/MC, 65

Functions

- · Smart Dimmable Constant Current Driver For LED Modules
- · Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- · Smooth Transition over wide range of CCT & Intensity
- · 1-100% Deep Dimming
- · High efficiency >88%(@100% Load)
- · Surge Protection Upto 4KV

Model No.	Watt Pout	O/P Voltage Voυτ (V)	O/P Current lout (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
VS36NHIBLE80450F (Only Dimming)	30-36	66-80	450	>88	>0.98	4	2	182*31*25mm
VS36NHIBLECCT80450F	30-36	66-80	450	>88	>0.98	4	2	182*31*25mm



Spotlight



Downlight



Linear



Decorative



Panel Light

WHY CHOOSE COLOSSUS?

Legacy of Innovation:

Each Driver we craft, ensures top-notch performance and technology.

Unwavering Quality Commitment:

Our products undergo rigorous testing. We confidently stand behind our quality with warranty.

Values and Integrity:

At Colossus, acting with "good faith" and advancing the industry's interests is our core ethos.

Our adaptability and continuous evolution with latest technologies are driven by our pursuit of excellence.



PRO SPECTRA (SMPS)



Functions

- · Constant voltage driver for LED modules
- · Compatible upto 5 Channel Control
- High efficiency >85%(@100% Load)
- For use in combination with luminaries of protection class II.
- · Surge Protection Upto 2.5KV

Model No.	Watt Pout	O/P Voltage Voυτ (V)	O/P Current Ιουτ (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
VS12ISIBLE5CH121000F	12	12	1000	>85	>0.50	2.5	2	182*31*25mm
VS30ISIBLE5CH122500F	30	12	2500	>85	>0.50	2.5	2	182*31*25mm
VS60ISIBLE5CH125000F	60	12	5000	>85	>0.50	2.5	2	211*36*30mm

COLDSSIS® Model No. Excellence inside: VS24ISIBLESCH241000F Input: Us: 124W0C, 894 k: 12.82 A. Pus.: 1200 A.>.0.90 Tought Vs: 124W0C to us: 12.4 Pus: 1200 A.>.0.90 Tought Vs: 124W0C to us: 124W0C to us: 124 Pus: 124W0C To us: 0.-r 4FC to us: 18FC to us: 18F

Functions

- · Constant voltage driver for LED modules
- · Compatible upto 5 Channel Control
- High efficiency >85%(@100% Load)
- · Constant Current Mode at Max Load Condition
- For use in combination with luminaries of protection class II.
- · Surge Protection Upto 2.5KV

Model No.	Watt Pout	O/P Voltage Vout (V)	O/P Current Іоυт (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
VS24ISIBLE5CH241000F	24	24	1000	>85	>0.50	2.5	2	182*31*25mm
VS60ISIBLE5CH242500F	60	24	2500	>85	>0.50	2.5	2	211*36*30mm







LED Strip Light

EXPLORE OUR STANDARD DRIVERS & SMPS AT COLOSSUSWORLD.COM

Head Office: #809/810, 8th Floor, Tower-B, Lodha Buisness District, Kolshet Road, Thane West - 400607 Call: +91-22-4964 9090 / 9191 OR +91-8291898747 / +91-7738087471

Kindly Contact for Dealership & Distribution on: connect@colossusworld.com