


COLOSSUSTM


Excellence inside

DATASHEET

US10IPI40250F



Version: 01



<https://colossusworld.com/>

*Image is for viewing purpose. Technical Data not to be drawn from above image.

Approval Markings:



Product Description

- Constant current driver for led modules
- Input voltage 240VAC
- High efficiency >86%(@100% Load)
- Power factor >0.85(@100%Load)
- For use in combination with luminaries of protection class II.
- Protection against Abnormal Operating Conditions Like Short Circuit Protection, Open Voltage Protection, Overload Protection.
- Surge protection 3KV
- Nominal Life Time: 30,000 hours @ $tc \leq tc_{max}$

Functions

- Application oriented operation for maximum compatibility

Applications



Office

Shops

House

Technical Data

Mains Voltage Supply

Rated Voltage Range	240VAC
Rated Frequency	50/60 Hz
Max. Admissible Input Voltage Range(AC)	175-265VAC
Total Harmonic Distortion (THD)	<60% (@Full Load)
Mains Voltage Withstanding Capacity	320VAC for 8hrs (with overvoltage shutdown)

Output Data

Constant current

Output Current Tolerance	±5%
Max Starting Time	<1s

Interface And Dimming Operation

Dimming Interface	None
-------------------	------

Power Factor

240V(@ Full Load)	>0.85
-------------------	-------

Efficiency(typ.)

Full Load	>86%
-----------	------

Protections

Open Circuit	<55VDC
Output Short Circuit Operation	YES
Input Over Voltage Cutoff	NA
Input Under Voltage Cutoff	NA

Connection Terminals

	For solid Or stranded wire
Type	Push Terminal
Wire Cross Section	0.5mm ² - 1.5mm ²
Wire Stripping Length	8.5mm - 9.5mm

Wire Lengths

Max. Wire Length To Led Module	<1m
--------------------------------	-----

Protection

Surge	3kV
High Voltage	320V

Temperatures (Operation)

Model No.	Ambient(ta)	Case (tc)
US10IPI40250F	0°C... +50°C	Max + 75°C


Product Specifications

Model No.	Input Current (max)	Input Power (max)	THD	Power Factor	Efficiency	Output Current	Output Voltage	Output Power (max)
US10IPI40250F	60mA	12W	<60%	>0.85	>86%	250mA	27-40V	10W


All specifications with 240 VAC are nominal operation and 100% load.

Graphs

Operating Window




Efficiency Vs Output Power



Housing Properties


Degree of protection	IP20
Casing	Polycarbonate, White

Housing Dimensions



Dimensions	108x21x21mm
Tolerance	± 1mm
Weight	40 gm

Wiring Diagrams



Expected Lifetime

Lifetime	30,000 hours
Warranty	2 years

Logistics Data

Model No.	US10IP140250F
Weight (gm)	40 gm