


COLOSSUSTM


Excellence inside

DATASHEET

VS60ISI242500F



Version: 01



<https://colossusworld.com/>

*Image is for viewing purpose. Technical Data not to be drawn from above image.

Approval Markings:



Product Description

- CV/CC Driver for led modules
- Input Voltage 240VAC
- High efficiency >90%(@100% Load)
- Power factor >0.50 (@100%Load)
- For use in combination with luminaries of protection class II.
- Protection against Abnormal Operating Conditions Like Open Voltage Protection, Overload Protection & Short Circuit Protection.
- Surge protection 4KV
- Nominal Life Time: 30,000 hours @ $t_c \leq t_{c \max}$

Functions

- Application oriented operation for maximum compatibility

Applications



Office



Shops



House

Technical Data

Mains Voltage Supply

Rated Voltage Range	240VAC
Rated Frequency	50/60 Hz
Max. Admissible Input Voltage Range(AC)	175-265VAC
Mains Voltage Withstanding Capacity	320VAC for 2hrs

Output Data

Constant current

Output Current Tolerance	±5%
Max Starting Time	<1s

Interface And Dimming Operation

Dimming Interface	None
-------------------	------

Power Factor

240V(@ Full Load)	>0.50
-------------------	-------

Efficiency(typ.)

Full Load	>90%
-----------	------

Protections

Open Circuit	<25VDC
Output Short Circuit Operation	Yes
Input Over Voltage Cutoff	None
Input Under Voltage Cutoff	None

Connection Wires

Type	Terminal Block
Wire Cross Section	0.5mm ² - 1.5mm ²
Wire Length	130mm (±10mm)

Wire Lengths

Max. Wire Length To Led Module	<1m
--------------------------------	-----

Protection

Surge	4kV
High Voltage	320V

Temperatures (Operation)

Model No.	Ambient(ta)	Case (tc)
VS60ISI242500F	0°C... +50°C	Max + 85°C


Product Specifications

Model No.	Input Current (max)	Input Power (max)	THD	Power Factor	Efficiency	Output Current	Output Voltage	Output Power (max)
VS60ISI242500F	420mA	65W	N.A	>0.50	>90%	2500mA	24V	60W


All specifications with 240 VAC are nominal operation and 100% load.

Graphs


Operating Window (CV)



Efficiency Vs Output Power




Operating Window (CC)



Housing Properties


Degree of protection	IP20
Casing	Polycarbonate, White

Housing Dimensions



Dimensions	148*40*30mm
Tolerance	± 1mm
Weight	150 gm

Wiring Diagrams



Expected Lifetime

Lifetime	30,000 hours
Warranty	2 years

Logistics Data

Model No.	VS60ISI242500F
Weight (gm)	150 gm