

COLOSSUS[®]

Excellence inside



Smart Wireless LED Drivers Technology



plexilent
simplifying life



CASAMBI

colossusworld.com

ABOUT COLOSSUS

Colossus Drivers: Powering the Future of LED Technology

At Colossus, we believe in crafting solutions that light the way to a brighter, more sustainable future. As a proudly Indian brand, we are committed to designing and manufacturing high-quality LED drivers that combine cutting-edge technology with a focus on reliability and efficiency.

Our journey has been one of continuous improvement, innovation, and dedication to quality. With the recent establishment of our first factory dedicated solely to Colossus Drivers, we are strengthening our roots in India's manufacturing landscape, ensuring that every product we create meets the highest standards of performance and sustainability. This milestone represents our ongoing effort to contribute to the 'Make in India' initiative, focusing on local production and energy-efficient technologies.

Our product range includes both Smart and Standard Drivers, developed to cater to the evolving needs of modern lighting solutions. Colossus Smart Drivers, available in Isolated and Non-Isolated formats, integrate seamlessly with mobile apps and smart home systems, offering advanced features like Surge Protection and High Voltage Protection. For those seeking dependable and straightforward solutions, our Standard Drivers provide reliability and efficiency, supporting eco-conscious living.

Colossus Drivers is more than a brand – it's a commitment to fostering innovation and providing dependable, Made-in-India products that contribute to a sustainable future. As we continue to grow, we invite you to join us on this journey, exploring new possibilities in lighting with technology-driven solutions designed to last.





COLOSSUS[®]

Excellence inside

COLOSSUS[®]

Excellence inside

“Achieve Lighting Excellence Like Never Before”



At Colossus, our focus has always been on delivering LED drivers that combine precision, quality, and innovation. From the beginning, we’ve been committed to developing solutions that meet the evolving demands of modern lighting with reliability and intelligent design. Each product we create undergoes rigorous testing, ensuring it meets the highest industry standards for performance and durability.

As we continue our journey, we remain dedicated to exploring new advancements in smart lighting systems, expanding our offerings to align with future demands. We view progress as a continuous process, one that encourages us to refine our approach and adapt to the latest trends and technologies.

At Colossus, customer trust and satisfaction are at the heart of what we do. Our mission is to support your lighting needs with products that stand the test of time, backed by reliable service and support. We look forward to moving ahead with you, shaping a future where quality and innovation light the way forward.

Thank you for choosing Colossus.



*KULDEEP GUPTA - Managing Director,
Lumens Technologies*

CONTENT

BEACON SMART LED DRIVER

● **PRO STATIC** (Fixed Output Current Drivers) ----- 1-2

BLE MESH SMART LED DRIVERS & SMPS


● **PRO FLEX** (Adjustable Output Current Drivers) ----- 3-7

● **PRO STATIC** (Fixed Output Current Drivers) ----- 8-11

● **PRO SPECTRA** (Smart SMPS) ----- 12-13


● **UPCOMING DRIVERS** ----- 14

CERTIFICATES






BEACON TECHNOLOGY



plexilent[®]
simplifying life

01.1 PRO STATIC FIXED CURRENT DRIVERS

WARRANTY:
> 1 YEAR




TO KNOW MORE
ABOUT PRODUCT



SCAN THE QR

■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE Beacon.
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency >90%(@100% Load)
- Surge Protection 2.5KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
LS24NSIBEACCT80300F	8-24	30-80	300	>90	>0.50	2.5	1	97.5*40*28mm



Spotlight



Downlight



Linear



Decorative

RoHS



IP20 SELV



SMART LED DRIVERS & SMPS


plexilent |  | CASAMBI
 simplifying life



COLOSSUS
 Excellence inside
 Model No. LS12AHBLECCT40300F
 Input U_{in} : 240VAC, 50Hz
 I_{in} : 0.065 A
 $P_{in\ max}$: 15W
 I_a : 0 ... + 50°C
 t_c : 75°C
 Output U_{out} : 27-40VDC
 I_{out} : 300mA
 P_{out} : 12W
 $U_{out\ max}$: 40VDC
 t_c : 75°C
 MADE IN INDIA
 IS 15188
 Part No. LS12013
 www.hls.gov.in


DS Output Current Settings	
SW1	SW2
OFF	OFF
OFF	DN
ON	OFF
ON	DN
ON	ON

COLOSSUS
 Excellence inside
 Model No. VS24IHBLECCT40600A
 Input U_{in} : 240 VAC, 50Hz
 I_a : 0 ... + 50°C
 t_c : 75°C
 Output U_{out} : 27-40VDC
 I_{out} : 300-600mA
 P_{out} : 27W / $I_a > 0.98$
 P_{out} : 12-24W
 $U_{out\ max}$: 40VDC
 MADE IN INDIA
 Dimmable Constant Current Led Driver
 IS 15188
 Part No. VS24013
 www.hls.gov.in

01.2 PRO FLEX ADJUSTABLE CURRENT DRIVERS

WARRANTY:
> 2 YEARS

PRO FLEX




TO KNOW MORE
ABOUT PRODUCT



SCAN THE QR

■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- Adjustable output current with Dip Switch.
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency >88%(@100% Load)
- Surge Protection 4KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
VS24IHIBLE40600A (Only Dimming)	12-24	27-40	300-600	>88	>0.98	4	2	150*40*28.5mm
VS24IHIBLECCT40600A	12-24	27-40	300-600	>88	>0.98	4	2	150*40*28.5mm
VS40IHIBLE401000A (Only Dimming)	28-40	27-40	700-1000	>88	>0.98	4	2	150*40*28.5mm
VS40IHIBLECCT401000A	28-40	27-40	700-1000	>88	>0.98	4	2	150*40*28.5mm



Spotlight



Downlight



Linear



Decorative

RoHS



IP20

SELV



01.2 PRO FLEX

ADJUSTABLE CURRENT DRIVERS

FLICKER FREE

**WARRANTY:
5 YEARS**




TO KNOW MORE ABOUT PRODUCT



SCAN THE QR

Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- Adjustable output current with Dip Switch
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency >85%(@100% Load)
- Surge Protection 4KV
- Low Ripple Current (<5%)



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (kV)	Burst Protection (kV)	Nominal Lifetime	Dimensions
ESS24IHISMACCT40600A	12-24	27-40	300-600	>85	>0.95	4	2	50000H	103*67.5*32mm
ESS40IHISMACCT401000A	28-40	27-40	700-1000	>85	>0.95	4	2	50000H	103*67.5*32mm




01.2 PRO FLEX

ADJUSTABLE CURRENT DRIVERS

FLICKER FREE

**WARRANTY:
5 YEARS**



TO KNOW MORE ABOUT PRODUCT




SCAN THE QR

PRO FLEX

■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- Adjustable output current with Dip Switch
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency >85%(@100% Load)
- Surge Protection 4KV
- Low Ripple Current (<5%)



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (kV)	Burst Protection (kV)	Nominal Lifetime	Dimensions
EVS24IHISMA40600A (Only Dimming)	12-24	27-40	300-600	>85	>0.95	4	2	50000H	150*40*28.5mm
EVS24IHISMACCT40600A	12-24	27-40	300-600	>85	>0.95	4	2	50000H	150*40*28.5mm
EVS40IHISMA401000A (Only Dimming)	28-40	27-40	700-1000	>85	>0.95	4	2	50000H	150*40*28.5mm
EVS40IHISMACCT401000A	28-40	27-40	700-1000	>85	>0.95	4	2	50000H	150*40*28.5mm



Spotlight



Downlight



Linear



Decorative




01.2 PRO FLEX

ADJUSTABLE CURRENT DRIVERS


FLICKER FREE

**WARRANTY:
5 YEARS & 3 YEARS**



■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE
- Adjustable output current with Dip Switch
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency upto >88%(@100% Load)
- Surge Protection 4KV
- Low Ripple Current (<5%)



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (kV)	Burst Protection (kV)	Nominal Lifetime	Dimensions
EUS12IHIBLECCT42300A	12	6-42	150-300	>85	>0.95	3	2	50000H	130*30*20mm
EUS25IHIBLECCT42600A	25	6-42	300-600	>85	>0.95	4	2	50000H	146*36*25mm
EUS36IHIBLECCT421050A	36	6-42	700-1050	>86	>0.95	4	2	50000H	166*40*28mm
EUS42IHIBLECCT541050A	42	6-54	700-1050	>88	>0.95	4	2	50000H	190*42*28mm



Spotlight



Downlight



Linear



Decorative

RoHS




IP20 SELV



01.3 PRO STATIC FIXED CURRENT DRIVERS

WARRANTY:
> 2 YEARS



TO KNOW MORE
ABOUT PRODUCT




SCAN THE QR

PRO STATIC

■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency Upto 85%(@100% Load)
- Surge Protection Upto 2.5KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
US06ISIBLECCT38150F	6	34-38	150	>85	>0.50	4	2	108x21x21mm
US08ISIBLECCT38200F	8	34-38	200	>85	>0.50	4	2	108x21x21mm



Spotlight



Downlight



Linear



Decorative




IP20 SELV



01.3 PRO STATIC FIXED CURRENT DRIVERS

WARRANTY:
> 2 YEARS



TO KNOW MORE
ABOUT PRODUCT




SCAN THE QR

PRO STATIC

■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency Upto 88%(@100% Load)
- Surge Protection Upto 4KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
LS08IHIBLECCT40200F	8	27-40	200	>85	>0.98	4	2	97.5*40*28mm
LS10IHIBLECCT40250F	10	27-40	250	>88	>0.98	4	2	97.5*40*28mm
LS12IHIBLECCT40300F	12	27-40	300	>88	>0.98	4	2	97.5*40*28mm
LS15IHIBLECCT40350F	14	27-40	350	>88	>0.98	4	2	97.5*40*28mm
LS15ISIBLECCT40350F	13	36	350	>82	>0.50	2.5	2	97.5*40*28mm



Spotlight



Downlight



Linear




Decorative



01.3 PRO STATIC FIXED CURRENT DRIVERS

WARRANTY:
> 2 YEARS




TO KNOW MORE
ABOUT PRODUCT



SCAN THE QR

■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency >88%(@100% Load)
- Surge Protection upto 4KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
SS15NSIBLECCT75200F	12-15	60-75	200	>87	>0.50	2.5	2	79*38*26.5mm
SS15NHIBLECCT75200F	12-15	60-75	200	>88	>0.98	4	2	79*38*26.5mm
SS15NSIBLECCT50300F	9-15	30-50	300	>87	>0.50	2.5	2	79*38*26.5mm
SS15NHIBLECCT50300F	9-15	30-50	300	>87	>0.98	4	2	79*38*26.5mm



Spotlight



Downlight



Linear



Decorative



01.3 PRO STATIC FIXED CURRENT DRIVERS

WARRANTY:
> 2 YEARS



TO KNOW MORE
ABOUT PRODUCT




SCAN THE QR

PRO STATIC

■ Functions

- Smart Dimmable Constant Current Driver For LED Modules
- Compatible with BLE, BLE MESH, ZIGBEE & WIFI Module
- Smooth Transition over wide range of CCT & Intensity
- 1-100% Deep Dimming
- High efficiency >90%(@100% Load)
- Surge Protection Upto 4KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
VS36NHIBLECCT80450F (Only Dimming)	30-36	66-80	450	>90	>0.98	4	2	182*31*25mm
VS36NHIBLECCT80450F	30-36	66-80	450	>90	>0.98	4	2	182*31*25mm



Spotlight



Downlight



Linear



Decorative

RoHS



IP20



**SMOOTH
SUPPLY**



**SLEEK
DESIGN**

PRO SPECTRA SMART SMPS

WHERE INNOVATION MEETS VIBRANT EFFICIENCY!

01.4 PRO SPECTRA SMART SMPS

**WARRANTY:
2 YEARS**




TO KNOW MORE ABOUT PRODUCT



SCAN THE QR

■ Functions

- Constant voltage driver for LED modules
- Compatible upto 5 Channel Control
- High efficiency >84%(@100% Load)
- For use in combination with luminaries of protection class II.
- Surge Protection Upto 4KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
VS60ISIBL5CH125000F	60	12	5000	>84	>0.50	4	2	212*42*31mm
VS60ISIBL5CH242500F	60	24	2500	>90	>0.50	4	2	212*42*31mm



Wall Washer



LED Strip Light



IP20 SELV



01.5 PRO SPECTRA

SMART SMPS


WARRANTY:
> 2 YEARS



PRO SPECTRA

■ Functions

- Constant voltage driver for LED modules
- Compatible upto 5 Channel Control
- High efficiency >85%(@100% Load)
- For use in combination with luminaries of protection class II.
- Surge Protection Upto 4KV



Model No.	Watt P _{OUT}	O/P Voltage V _{OUT} (V)	O/P Current I _{OUT} (mA)	Efficiency (%)	Power Factor	Surge Protection (KV)	Warranty (Years)	Dimensions
US60IHIBLE5CH125000F	60	12	5000	>85	>0.9	4	2	230*42*28mm
US100IHIBLE5CH128300F	100	12	8300	>85	>0.9	4	2	285*40*31mm
US150IHIBLE5CH1212500F	150	12	12500	>85	>0.9	4	2	340*40*31mm
US60IHIBLE5CH242500F	60	24	2500	>85	>0.9	4	2	230*42*28mm
US100IHIBLE5CH244200F	100	24	4200	>85	>0.9	4	2	285*40*31mm
US150IHIBLE5CH246200F	150	24	6200	>85	>0.9	4	2	340*40*31mm



Wall Washer



LED Strip Light



IP20 SELV





COLOSSUS®

Excellence inside



Explore Partnership Opportunities With Us!

For **Dealership And Distribution** Inquiries,
Please Reach Us At: connect@colossusworld.com



plexilent
simplifying life



CASAMBI

Head Office: #809/810, 8th Floor, Tower-B,
Lodha Business District, Kolshet Road, Thane West - 400607
Call: +91-8291898747 / +91-7738087471

colossusworld.com