COLOSSUS® Excellence inside



DALI-2 NFC LED Drivers Technology





ABOUT COLOSSUS

Colossus Drivers: Powering the Future of LED Technology

Colossus is a technology-led Indian brand focused on designing and manufacturing high-performance LED drivers built for reliability, efficiency, and seamless integration. With our dedicated manufacturing facility, we are strengthening India's role in global electronics and advancing the 'Make in India' initiative through local, energy-efficient production.

Our portfolio includes Smart and Standard Drivers tailored for modern lighting systems. Smart Drivers: offered in both Isolated and Non-Isolated formats connect with mobile apps and smart home platforms, and include built-in Surge and High Voltage Protection. Standard Drivers are optimized for long-term efficiency and dependable performance.

Colossus represents a shift towards smarter, future-ready lighting infrastructure, driven by innovation, backed by quality, and engineered to last.







Flicker Free



Global Compatibility



Longetivity & Reliability







DALI-2













All Colossus Drivers comply with industry standards and are certified for quality, safety, and performance.







































NFC))) IP20 SELV



WIRED SMART DRIVERS



DALI-2 NFC (DT-6)

ADJUSTABLE CURRENT DRIVERS

FLICKER FREE WARRANTY:



Functions

- · DALI-2 + PUSH Dim constant current LED drivers
- · Parameters programmable via NFC (Output Current, CLO, Dimming Curve, Min/Max level, Groups, and Scenes etc)
- · Flicker-free with Smooth Dimming and On/Off control
- · High reliability with a nominal lifetime of 50,000 hours
- · Suitable for use with luminaires of protection class II
- · Deep Dimming 1%-100%

| Model No. | Watt Pout | O/P Voltage Vout (V) | O/P Current Ιουτ (mA) | Efficiency (%) | Power Factor | Surge Protection (KV) | Warranty (Years) | Dimensions (Built-in) |
|--------------------|--------------|----------------------------|-----------------------------|-------------------|-----------------|-----------------------------|---------------------|--------------------------|
| ELS151H1DT646350N | 15 | 3-46V | 100-350 | >85 | >0.94 | 2 | 5 | 118.3*31*21.5mm |
| ELS21IHIDT645500A | 21 | 15-45V | 150-500 | >87 | >0.95 | 2 | 5 | 97.5*44*23mm |
| ELS23IHIDT646700N | 23 | 3-46V | 100-700 | >86 | >0.95 | 2 | 5 | 118.3*31*21.5mm |
| ELS36IHIDT650900N | 36 | 3-50V | 150-900 | >88 | >0.95 | 2 | 5 | 143.3*31*21.5mm |
| ELS44IHIDT6491050A | 44 | 9-49V | 700-1050 | >90 | >0.97 | 2 | 5 | 97.5*44*23mm |

Note: Above Model Numbers ending with denotion "A" are DIP Switch based current adjustable.



DALI-2 NFC (DT-8) ADJUSTABLE CURRENT DRIVERS

FLICKER FREE





Functions

- · DALI-2 + PUSH Dim constant current LED drivers
- · Parameters programmable via NFC (Output Current, CLO, Dimming Curve, Min/Max level, Groups, and Scenes etc)
- · Flicker-free with Smooth Dimming, CCT and On/Off control
- · High reliability with a nominal lifetime of 50,000 hours
- · Suitable for use with luminaires of protection class II
- · Deep Dimming 1%-100%

| Model No. | Watt Pout | O/P Voltage Vout (V) | O/P Current Ιουτ (mA) | Efficiency (%) | Power Factor | Surge Protection (KV) | Warranty (Years) | Dimensions (Built-in) |
|--------------------|--------------|----------------------------|-----------------------------|-------------------|-----------------|-----------------------------|---------------------|--------------------------|
| ELS12IHIDT848400N | 12 | 4-48V | 100-400 | >85 | >0.90 | 2 | 5 | 118.3*31*21.5mm |
| ELS20IHIDT846700N | 20 | 3-46V | 350-700 | >87 | >0.93 | 2 | 5 | 143.3*31*21.5mm |
| ELS30IHIDT842900N | 30 | 9-42V | 200-900 | >89 | >0.97 | 2 | 5 | 122.5*44*23mm |
| ELS42IHIDT8421050N | 42 | 10-42V | 300-1050 | >90 | >0.97 | 2 | 5 | 122.5*44*23mm |

DALI-2 NFC (DT-6) ADJUSTABLE CURRENT DRIVERS

FLICKER FREE





Functions

- · DALI-2 + PUSH Dim constant current LED drivers
- · Parameters programmable via NFC (Output Current, CLO, Dimming Curve, Min/Max level, Groups, and Scenes etc)
- Flicker-free with Smooth Dimming and On/Off control
- · High reliability with a nominal lifetime of 50,000 hours
- $\cdot \textit{Suitable for use with luminaires of protection class II} \\$
- · Deep Dimming 1%-100%

| Model No. | Watt Pout | O/P Voltage Vout (V) | O/P Current lout (mA) | Efficiency (%) | Power Factor | Surge Protection (KV) | Warranty (Years) | Dimensions (Built-in) |
|------------------|--------------|----------------------------|-----------------------------|-------------------|-----------------|-----------------------------|---------------------|--------------------------|
| RS10IHIDT648500N | 10 | 3-48V | 100-500 | >80 | >0.85 | 1 | 5 | Ф 42X21mm(RXH) |
| RS18IHIDT648700N | 18 | 3-48V | 300-700 | >82 | >0.90 | 2 | 5 | Ф 55X25mm(RXH) |



WIRED SMART SMPS



 \neg

DALI-2 (DT-6) SMART SMPS

FLICKER FREE





Functions

- · DALI-2 + PUSH Dim constant current LED drivers
- Flicker-free with Smooth Dimming and On/Off control
- · High Power Factor and Low THD
- · High reliability with a nominal lifetime of 50,000 hours
- · Suitable for use with luminaires of protection class II
- · Deep Dimming 1%-100%

| Model No. | Watt Pout | O/P Voltage Vout (V) | O/P Current Ιουτ (A) | Efficiency (%) | Power Factor | Surge Protection (KV) | Warranty (Years) | Dimensions (Built-in) |
|--------------------|--------------|----------------------------|----------------------------|-------------------|-----------------|-----------------------------|---------------------|--------------------------|
| US1001HIDT6244170F | 100 | 24V | 4.17 | >93 | >0.95 | 2 | 5 | 286*42*31mm |
| US150IHIDT6246250F | 150 | 24V | 6.25 | >93 | >0.97 | 2 | 5 | 286*42*31mm |
| US200IHIDT6248330F | 200 | 24V | 8.33 | >93 | >0.97 | 2 | 5 | 286*42*31mm |

DALI-2 (DT-8) SMART SMPS

FLICKER FREE





Functions

- · DALI-2 + PUSH Dim constant voltage LED drivers
- $\cdot \textit{Flicker-free with Smooth Dimming, CCT and On/Off control}\\$
- · High Power Factor and Low THD
- $\cdot \textit{ High reliability with a nominal lifetime of 50,000 hours}\\$
- · Suitable for use with luminaires of protection class II
- · Deep Dimming 1%-100%

| Model No. | Watt Pout | O/P Voltage Vout (V) | O/P Current Ιουτ (A) | Efficiency (%) | Power Factor | Surge Protection (KV) | Warranty (Years) | Dimensions (Built-in) |
|--------------------|--------------|----------------------------|----------------------------|-------------------|-----------------|-----------------------------|---------------------|--------------------------|
| US100IHIDT8244170F | 100 | 24V | 4.17 | >93 | >0.95 | 2 | 5 | 286*42*31mm |
| US150IHIDT8246250F | 150 | 24V | 6.25 | >93 | >0.97 | 2 | 5 | 286*42*31mm |
| US200IHIDT8248330F | 200 | 24V | 8.33 | >93 | >0.97 | 2 | 5 | 286*42*31mm |



48V MAGNETIC DRIVER



DALI-2 (DT6 & DT8)
48V DC-DC MAGNETIC DRIVER

FLICKER FREE





Functions

- · DALI-2 + PUSH Dim 48V DC-DC convertor
- Flicker-free with Smooth Dimming, CCT and On/Off control
- · High reliability with a nominal lifetime of 50,000 hours
- · Adjustable Output Current via DIP switch
- · Deep Dimming 1%-100%

| Model No. | Watt Pour | O/P Voltage Vout (V) | O/P Current lour (mA) | Efficiency (%) | Power Factor | Surge Protection (KV) | Warranty (Years) | Dimensions (Built-in) |
|------------------|--------------|----------------------------|-----------------------------|-------------------|-----------------|-----------------------------|---------------------|--------------------------|
| OD18NIDT642700A | 18 | 10-42 | 100-700 | >93 | NA | NA | 5 | 125*13.5*10.43mm |
| OD32NIDT642700A | 32 | 10-42 | 100-700 | >95 | NA | NA | 5 | 125*13.5*10.43mm |
| OD42NIDT6421050A | 42 | 10-42 | 450-1050 | >95 | NA | NA | 5 | 125*13.5*10.43mm |
| OD18NIDT842700A | 18 | 10-42 | 100-700 | >93 | NA | NA | 5 | 125*13.5*10.43mm |
| OD32NIDT842700A | 32 | 10-42 | 100-700 | >95 | NA | NA | 5 | 125*13.5*10.08mm |
| OD42NIDT8421050A | 42 | 10-42 | 450-1050 | >95 | NA | NA | 5 | 125*13.5*10.08mm |



COLOSSUS Excellence inside

Explore Partnership Opportunities With Us!

For **Dealership And Distribution** Inquiries, Please Reach Us At: connect@colossusworld.com





Head Office: #809/810, 8th Floor, Tower-B, Lodha Business District, Kolshet Road, Thane West - 400607 Call: +91-8291898747 / +91-7738087471